



## PRODUCT INFORMATION SHEET

### Lubri/Stat®M2

---

**Description:** **Lubri/Sat®M2** is a high-performance food grade coating applied to the exterior of Polyethylene Terephthalate (PET) preforms and bottles. **Lubri/Stat®M2** is a proven surface coating system that creates a lubricious protective film that enhances bottle appearance, reduces both static charge & dust accumulation on the bottle wall, reduces sticking, scuffing & scratching that provides the user with superior bottle handling characteristics.

---

<b>Physical Properties:</b>	Appearance	- Light Yellow Liquid
	pH (as is)	- 4.0 – 6.0
	Density	- 0.9587 – 0.9880
	Viscosity (20 rpm)	- 80 -130 cP

---

**Typical Uses:** Polyethylene Terephthalate (PET) bottles, preforms, strapping other plastic polymers and glassware.

---

**Application:** **Lubri/Stat®M2** is a concentrate that is easy to mix and apply. We recommend **Lubri/Stat®M2** concentrate be diluted with 32 parts deionized water, occasionally agitating. **Lubri/Stat®M2** is applied utilizing the **Lubri/Stat®** Spray System - a unique precision on-line ultrasonic spray system which is simple to use and cost effective. The ultrasonic spray nozzle keeps spray material and air consumption to a minimum. The construction of the unit is stainless steel.

---

**Storage & Handling:** For further information on storage, handling, hazards, etc. please refer to safety data sheet.

---

**Packaging:** **Lubri/Stat®M2** is available in 39.5 lbs. pail and 434 lbs. drum.

---

**Shelf Life:** Approximately 18 months as 100% concentrate.

---

JCL SPECIALTY PRODUCTS, INC. – 19106 S. Blackhawk Parkway – Mokena, IL 60448  
Phone: (815) 806-2202 Fax: (815) 806-2262

Lubri/Stat® is a registered trademark of JCL Specialty Products, Inc.