



PRODUCT INFORMATION SHEET

Lubri/Stat®M2

Description: Lubri/Sat®M2 is a high-performance food grade coating applied to the exterior of Polyethylene Terephthalate (PET) preforms and bottles. Lubri/Stat®M2 is a proven surface coating system that creates a lubricious protective film that enhances bottle appearance, reduces both static charge & dust accumulation on the bottle wall, reduces sticking, scuffing & scratching that provides the user with superior bottle handling characteristics.

Physical Properties:	Appearance	- Light Yellow Liquid
	pH (as is)	- 4.0 – 6.0
	Density	- 0.9604 – 0.9950
	Viscosity (#3 Mini Ford Cup)	- 80 -200 CST

Typical Uses: Polyethylene Terephthalate (PET) bottles, preforms, other plastic polymers and glassware.

Application: Lubri/Stat®M2 is a concentrate that is easy to mix and apply. We recommend Lubri/Stat®M2 concentrate be diluted with 32 parts deionized water, occasionally agitating. Lubri/Stat®M2 is applied utilizing the Lubri/Stat® Spray System - a unique precision on-line ultrasonic spray system which is simple to use and cost effective. The ultrasonic spray nozzle keeps spray material and air consumption to a minimum. The construction of the unit is stainless steel.

Storage & Handling: For further information on storage, handling, hazards, etc. please refer to safety data sheet.

Packaging: Lubri/Stat®M2 is available in 39.5 lbs. pail and 434 lbs. drum.

Shelf Life: Approximately 18 months as 100% concentrate.

JCL SPECIALTY PRODUCTS, INC. – 19131 S. Blackhawk Parkway – Mokena, IL 60448
Phone: (815) 806-2202 Fax: (815) 806-2262

Lubri/Stat® is a registered trademark of JCL Specialty Products, Inc.